


**2-1** The center portion of the rubber balloon has a diameter of  $d = 100$  mm. If the air pressure within it causes the balloon's diameter to become  $d = 125$  mm, determine the average normal strain in the rubber.

**Given:**  $d_0 := 100\text{mm}$       $d := 125\text{mm}$

**Solution:**

$$\varepsilon := \frac{\pi d - \pi d_0}{\pi d_0}$$

$$\varepsilon = 0.2500 \frac{\text{mm}}{\text{mm}} \quad \text{Ans}$$



**Ans:**

$$\epsilon_{CE} = 0.00250 \text{ mm/mm}, \epsilon_{BD} = 0.00107 \text{ mm/mm}$$

**2-2.** A thin strip of rubber has an unstretched length of 375 mm. If it is stretched around a pipe having an outer diameter of 125 mm, determine the average normal strain in the strip.

$$L_0 = 375 \text{ mm}$$


$$L = \pi(125 \text{ mm})$$

$$\epsilon = \frac{L - L_0}{L_0} = \frac{125\pi - 375}{375} = 0.0472 \text{ mm/mm}$$

**Ans.**

**Ans:**  
 $\epsilon = 0.0472 \text{ mm/mm}$

**2-3.** The rigid beam is supported by a pin at *A* and wires *BD* and *CE*. If the load **P** on the beam causes the end *C* to be displaced 10 mm downward, determine the normal strain developed in wires *CE* and *BD*.



$$\frac{\Delta L_{BD}}{3} = \frac{\Delta L_{CE}}{7}$$


$$\Delta L_{BD} = \frac{3(10)}{7} = 4.286 \text{ mm}$$

$$\epsilon_{CE} = \frac{\Delta L_{CE}}{L} = \frac{10}{4000} = 0.00250 \text{ mm/mm}$$

**Ans.**

$$\epsilon_{BD} = \frac{\Delta L_{BD}}{L} = \frac{4.286}{4000} = 0.00107 \text{ mm/mm}$$


**Ans.**



**Ans:**

$$\epsilon_{CE} = 0.00250 \text{ mm/mm}, \epsilon_{BD} = 0.00107 \text{ mm/mm}$$

**\*2-4.** The force applied at the handle of the rigid lever causes the lever to rotate clockwise about the pin  $B$  through an angle of  $2^\circ$ . Determine the average normal strain developed in each wire. The wires are unstretched when the lever is in the horizontal position.



**Geometry:** The lever arm rotates through an angle of  $\theta = \left(\frac{2^\circ}{180}\right)\pi \text{ rad} = 0.03491 \text{ rad}$ .

Since  $\theta$  is small, the displacements of points  $A$ ,  $C$ , and  $D$  can be approximated by

$$\delta_A = 200(0.03491) = 6.9813 \text{ mm}$$

$$\delta_C = 300(0.03491) = 10.4720 \text{ mm}$$

$$\delta_D = 500(0.03491) = 17.4533 \text{ mm}$$


**Average Normal Strain:** The unstretched length of wires  $AH$ ,  $CG$ , and  $DF$  are

$L_{AH} = 200 \text{ mm}$ ,  $L_{CG} = 300 \text{ mm}$ , and  $L_{DF} = 300 \text{ mm}$ . We obtain


$$(\epsilon_{\text{avg}})_{AH} = \frac{\delta_A}{L_{AH}} = \frac{6.9813}{200} = 0.0349 \text{ mm/mm} \quad \text{Ans.}$$

$$(\epsilon_{\text{avg}})_{CG} = \frac{\delta_C}{L_{CG}} = \frac{10.4720}{300} = 0.0349 \text{ mm/mm} \quad \text{Ans.}$$

$$(\epsilon_{\text{avg}})_{DF} = \frac{\delta_D}{L_{DF}} = \frac{17.4533}{300} = 0.0582 \text{ mm/mm} \quad \text{Ans.}$$




**2-5.** The two wires are connected together at *A*. If the force **P** causes point *A* to be displaced horizontally 2 mm, determine the normal strain developed in each wire.



$$L'_{AC} = \sqrt{300^2 + 2^2 - 2(300)(2) \cos 150^\circ} = 301.734 \text{ mm}$$

$$\epsilon_{AC} = \epsilon_{AB} = \frac{L'_{AC} - L_{AC}}{L_{AC}} = \frac{301.734 - 300}{300} = 0.00578 \text{ mm/mm}$$

**Ans.**



**Ans:**

$$\epsilon_{AC} = \epsilon_{AB} = 0.00578 \text{ mm/mm}$$

**2-6.** The rubber band of unstretched length  $2r_0$  is forced down the frustum of the cone. Determine the average normal strain in the band as a function of  $z$ .

**Geometry:** Using similar triangles shown in Fig. *a*,

$$\frac{h'}{r_0} = \frac{h' + h}{2r_0}; \quad h' = h$$



Subsequently, using the result of  $h'$

$$\frac{r}{z + h} = \frac{r_0}{h}; \quad r = \frac{r_0}{h}(z + h)$$

**Average Normal Strain:** The length of the rubber band as a function of  $z$  is  $L = 2\pi r = \frac{2\pi r_0}{h}(z + h)$ . With  $L_0 = 2r_0$ , we have

$$\epsilon_{\text{avg}} = \frac{L - L_0}{L_0} = \frac{\frac{2\pi r_0}{h}(z + h) - 2r_0}{2r_0} = \frac{\pi}{h}(z + h) - 1$$


Ans.



Ans:

$$\epsilon_{\text{avg}} = \frac{\pi}{h}(z + h) - 1$$

**2-7.** The pin-connected rigid rods  $AB$  and  $BC$  are inclined at  $\theta = 30^\circ$  when they are unloaded. When the force  $\mathbf{P}$  is applied  $\theta$  becomes  $30.2^\circ$ . Determine the average normal strain developed in wire  $AC$ .




**Geometry:** Referring to Fig. *a*, the unstretched and stretched lengths of wire  $AD$  are

$$L_{AC} = 2(600 \sin 30^\circ) = 600 \text{ mm}$$

$$L_{AC'} = 2(600 \sin 30.2^\circ) = 603.6239 \text{ mm}$$

**Average Normal Strain:**


$$(\epsilon_{\text{avg}})_{AC} = \frac{L_{AC'} - L_{AC}}{L_{AC}} = \frac{603.6239 - 600}{600} = 6.04(10^{-3}) \text{ mm/mm} \quad \text{Ans.}$$



**Ans:**

$$(\epsilon_{\text{avg}})_{AC} = 6.04(10^{-3}) \text{ mm/mm}$$

**\*2-8.** Part of a control linkage for an airplane consists of a rigid member  $CBD$  and a flexible cable  $AB$ . If a force is applied to the end  $D$  of the member and causes it to rotate by  $\theta = 0.3^\circ$ , determine the normal strain in the cable. Originally the cable is unstretched.



$$AB = \sqrt{400^2 + 300^2} = 500 \text{ mm}$$


$$AB' = \sqrt{400^2 + 300^2 - 2(400)(300) \cos 90.3^\circ}$$

$$= 501.255 \text{ mm}$$

$$\epsilon_{AB} = \frac{AB' - AB}{AB} = \frac{501.255 - 500}{500}$$


$$= 0.00251 \text{ mm/mm}$$

**Ans.**





**2-9.** Part of a control linkage for an airplane consists of a rigid member  $CBD$  and a flexible cable  $AB$ . If a force is applied to the end  $D$  of the member and causes a normal strain in the cable of  $0.0035 \text{ mm/mm}$ , determine the displacement of point  $D$ . Originally the cable is unstretched.



$$AB = \sqrt{300^2 + 400^2} = 500 \text{ mm}$$

$$AB' = AB + \epsilon_{AB}AB$$

$$= 500 + 0.0035(500) = 501.75 \text{ mm}$$


$$501.75^2 = 300^2 + 400^2 - 2(300)(400) \cos \alpha$$

$$\alpha = 90.4185^\circ$$

$$\theta = 90.4185^\circ - 90^\circ = 0.4185^\circ = \frac{\pi}{180^\circ} (0.4185) \text{ rad}$$

$$\Delta_D = 600(\theta) = 600\left(\frac{\pi}{180^\circ}\right)(0.4185) = 4.38 \text{ mm}$$


**Ans.**



**Ans:**

$$\Delta_D = 4.38 \text{ mm}$$

**2-10.** The corners of the square plate are given the displacements indicated. Determine the shear strain along the edges of the plate at  $A$  and  $B$ .




At  $A$ :

$$\frac{\theta'}{2} = \tan^{-1} \left( \frac{9.7}{10.2} \right) = 43.561^\circ$$

$$\theta' = 1.52056 \text{ rad}$$

$$(\gamma_A)_{nt} = \frac{\pi}{2} - 1.52056$$

$$= 0.0502 \text{ rad}$$



**Ans.**


At  $B$ :

$$\frac{\phi'}{2} = \tan^{-1} \left( \frac{10.2}{9.7} \right) = 46.439^\circ$$

$$\phi' = 1.62104 \text{ rad}$$

$$(\gamma_B)_{nt} = \frac{\pi}{2} - 1.62104$$

$$= -0.0502 \text{ rad}$$




**Ans.**

**Ans:**

$$(\gamma_A)_{nt} = 0.0502 \text{ rad}, (\gamma_B)_{nt} = -0.0502 \text{ rad}$$

**2-11.** The corners  $B$  and  $D$  of the square plate are given the displacements indicated. Determine the average normal strains along side  $AB$  and diagonal  $DB$ .



Referring to Fig. a,

$$L_{AB} = \sqrt{16^2 + 16^2} = \sqrt{512} \text{ mm}$$

$$L_{AB'} = \sqrt{16^2 + 13^2} = \sqrt{425} \text{ mm}$$

$$L_{BD} = 16 + 16 = 32 \text{ mm}$$

$$L_{B'D'} = 13 + 13 = 26 \text{ mm}$$


Thus,

$$(\epsilon_{\text{avg}})_{AB} = \frac{L_{AB'} - L_{AB}}{L_{AB}} = \frac{\sqrt{425} - \sqrt{512}}{\sqrt{512}} = -0.0889 \text{ mm/mm}$$

**Ans.**

$$(\epsilon_{\text{avg}})_{BD} = \frac{L_{B'D'} - L_{BD}}{L_{BD}} = \frac{26 - 32}{32} = -0.1875 \text{ mm/mm}$$

**Ans.**




2-12

2-13

**Ans:**

$$\epsilon_{DB} = \epsilon_{AB} \cos^2 \theta + \epsilon_{CB} \sin^2 \theta$$

**2-14.** The force **P** applied at joint **D** of the square frame causes the frame to sway and form the dashed rhombus. Determine the average normal strain developed in wire **AC**. Assume the three rods are rigid.



**Geometry:** Referring to Fig. *a*, the stretched length of  $L_{AC'}$  of wire  $AC'$  can be determined using the cosine law.


$$L_{AC'} = \sqrt{400^2 + 400^2 - 2(400)(400) \cos 93^\circ} = 580.30 \text{ mm}$$

The unstretched length of wire  $AC$  is

$$L_{AC} = \sqrt{400^2 + 400^2} = 565.69 \text{ mm}$$

**Average Normal Strain:**


$$(\epsilon_{\text{avg}})_{AC} = \frac{L_{AC'} - L_{AC}}{L_{AC}} = \frac{580.30 - 565.69}{565.69} = 0.0258 \text{ mm/mm} \quad \text{Ans.}$$



**Ans:**

$$(\epsilon_{\text{avg}})_{AC} = 0.0258 \text{ mm/mm}$$

**2-15.** The force **P** applied at joint **D** of the square frame causes the frame to sway and form the dashed rhombus. Determine the average normal strain developed in wire **AE**. Assume the three rods are rigid.



**Geometry:** Referring to Fig. *a*, the stretched length of  $L_{AE'}$  of wire **AE** can be determined using the cosine law.


$$L_{AE'} = \sqrt{400^2 + 200^2 - 2(400)(200) \cos 93^\circ} = 456.48 \text{ mm}$$

The unstretched length of wire **AE** is

$$L_{AE} = \sqrt{400^2 + 200^2} = 447.21 \text{ mm}$$

**Average Normal Strain:**


$$(\epsilon_{\text{avg}})_{AE} = \frac{L_{AE'} - L_{AE}}{L_{AE}} = \frac{456.48 - 447.21}{447.21} = 0.0207 \text{ mm/mm} \quad \text{Ans.}$$



**Ans:**

$$(\epsilon_{\text{avg}})_{AE} = 0.0207 \text{ mm/mm}$$

**\*2-16.** The triangular plate  $ABC$  is deformed into the shape shown by the dashed lines. If at  $A$ ,  $\epsilon_{AB} = 0.0075$ ,  $\epsilon_{AC} = 0.01$  and  $\gamma_{xy} = 0.005$  rad, determine the average normal strain along edge  $BC$ .



**Average Normal Strain:** The stretched length of sides  $AB$  and  $AC$  are

$$L_{AC'} = (1 + \epsilon_y)L_{AC} = (1 + 0.01)(300) = 303 \text{ mm}$$

$$L_{AB'} = (1 + \epsilon_x)L_{AB} = (1 + 0.0075)(400) = 403 \text{ mm}$$

Also,

$$\theta = \frac{\pi}{2} - 0.005 = 1.5658 \text{ rad} \left( \frac{180^\circ}{\pi \text{ rad}} \right) = 89.7135^\circ$$

The unstretched length of edge  $BC$  is

$$L_{BC} = \sqrt{300^2 + 400^2} = 500 \text{ mm}$$


and the stretched length of this edge is

$$\begin{aligned} L_{B'C'} &= \sqrt{303^2 + 403^2 - 2(303)(403) \cos 89.7135^\circ} \\ &= 502.9880 \text{ mm} \end{aligned}$$

We obtain,


$$\epsilon_{BC} = \frac{L_{B'C'} - L_{BC}}{L_{BC}} = \frac{502.9880 - 500}{500} = 5.98(10^{-3}) \text{ mm/mm}$$

**Ans.**





**2-17.** The plate is deformed uniformly into the shape shown by the dashed lines. If at  $A$ ,  $\gamma_{xy} = 0.0075 \text{ rad}$ , while  $\epsilon_{AB} = \epsilon_{AF} = 0$ , determine the average shear strain at point  $G$  with respect to the  $x'$  and  $y'$  axes.



**Geometry:** Here,  $\gamma_{xy} = 0.0075 \text{ rad} \left( \frac{180^\circ}{\pi \text{ rad}} \right) = 0.4297^\circ$ . Thus,

$$\psi = 90^\circ - 0.4297^\circ = 89.5703^\circ$$

$$\beta = 90^\circ + 0.4297^\circ = 90.4297^\circ$$

Subsequently, applying the cosine law to triangles  $AGF'$  and  $GBC'$ , Fig.  $a$ ,

$$L_{GF'} = \sqrt{600^2 + 300^2 - 2(600)(300) \cos 89.5703^\circ} = 668.8049 \text{ mm}$$

$$L_{GC'} = \sqrt{600^2 + 300^2 - 2(600)(300) \cos 90.4297^\circ} = 672.8298 \text{ mm}$$

Then, applying the sine law to the same triangles,

$$\frac{\sin \phi}{600} = \frac{\sin 89.5703^\circ}{668.8049}; \quad \phi = 63.7791^\circ$$

$$\frac{\sin \alpha}{300} = \frac{\sin 90.4297^\circ}{672.8298}; \quad \alpha = 26.4787^\circ$$

Thus,


$$\theta = 180^\circ - \phi - \alpha = 180^\circ - 63.7791^\circ - 26.4787^\circ$$

$$= 89.7422^\circ \left( \frac{\pi \text{ rad}}{180^\circ} \right) = 1.5663 \text{ rad}$$

**Shear Strain:**

$$(\gamma_G)_{x'y'} = \frac{\pi}{2} - \theta = \frac{\pi}{2} - 1.5663 = 4.50(10^{-3}) \text{ rad}$$


**Ans.**



**Ans:**

$$(\gamma_G)_{x'y'} = 4.50(10^{-3}) \text{ rad}$$

**2-18.** The piece of plastic is originally rectangular. Determine the shear strain  $\gamma_{xy}$  at corners  $A$  and  $B$  if the plastic distorts as shown by the dashed lines.



**Geometry:** For small angles,


$$\alpha = \psi = \frac{2}{302} = 0.00662252 \text{ rad}$$

$$\beta = \theta = \frac{2}{403} = 0.00496278 \text{ rad}$$

**Shear Strain:**

$$\begin{aligned} (\gamma_B)_{xy} &= \alpha + \beta \\ &= 0.0116 \text{ rad} = 11.6(10^{-3}) \text{ rad} \end{aligned}$$

$$\begin{aligned} (\gamma_A)_{xy} &= \theta + \psi \\ &= 0.0116 \text{ rad} = 11.6(10^{-3}) \text{ rad} \end{aligned}$$



**Ans.**


**Ans.**

**Ans:**

$$(\gamma_B)_{xy} = 11.6(10^{-3}) \text{ rad},$$

$$(\gamma_A)_{xy} = 11.6(10^{-3}) \text{ rad}$$

**2-19.** The piece of plastic is originally rectangular. Determine the shear strain  $\gamma_{xy}$  at corners  $D$  and  $C$  if the plastic distorts as shown by the dashed lines.



**Geometry:** For small angles,

$$\alpha = \psi = \frac{2}{403} = 0.00496278 \text{ rad}$$

$$\beta = \theta = \frac{2}{302} = 0.00662252 \text{ rad}$$


**Shear Strain:**

$$\begin{aligned} (\gamma_C)_{xy} &= \alpha + \beta \\ &= 0.0116 \text{ rad} = 11.6(10^{-3}) \text{ rad} \end{aligned}$$

**Ans.**

$$\begin{aligned} (\gamma_D)_{xy} &= \theta + \psi \\ &= 0.0116 \text{ rad} = 11.6(10^{-3}) \text{ rad} \end{aligned}$$

**Ans.**




**Ans:**

$$(\gamma_C)_{xy} = 11.6(10^{-3}) \text{ rad},$$

$$(\gamma_D)_{xy} = 11.6(10^{-3}) \text{ rad}$$

**\*2-20.** The piece of plastic is originally rectangular. Determine the average normal strain that occurs along the diagonals  $AC$  and  $DB$ .



**Geometry:**

$$AC = DB = \sqrt{400^2 + 300^2} = 500 \text{ mm}$$

$$DB' = \sqrt{405^2 + 304^2} = 506.4 \text{ mm}$$

$$A'C' = \sqrt{401^2 + 300^2} = 500.8 \text{ mm}$$


**Average Normal Strain:**

$$\begin{aligned} \epsilon_{AC} &= \frac{A'C' - AC}{AC} = \frac{500.8 - 500}{500} \\ &= 0.00160 \text{ mm/mm} = 1.60(10^{-3}) \text{ mm/mm} \end{aligned}$$


$$\begin{aligned} \epsilon_{DB} &= \frac{DB' - DB}{DB} = \frac{506.4 - 500}{500} \\ &= 0.0128 \text{ mm/mm} = 12.8(10^{-3}) \text{ mm/mm} \end{aligned}$$

**Ans.**

**Ans.**



**2-21.** The rectangular plate is deformed into the shape of a parallelogram shown by the dashed lines. Determine the average shear strain  $\gamma_{xy}$  at corners  $A$  and  $B$ .



**Geometry:** Referring to Fig. *a* and using small angle analysis,

$$\theta = \frac{5}{300} = 0.01667 \text{ rad}$$

$$\phi = \frac{5}{400} = 0.0125 \text{ rad}$$


**Shear Strain:** Referring to Fig. *a*,

$$(\gamma_A)_{xy} = \theta + \phi = 0.01667 + 0.0125 = 0.0292 \text{ rad}$$

**Ans.**

$$(\gamma_B)_{xy} = \theta + \phi = 0.01667 + 0.0125 = 0.0292 \text{ rad}$$


**Ans.**



**Ans:**

$$(\gamma_A)_{xy} = 0.0292 \text{ rad}, (\gamma_B)_{xy} = 0.0292 \text{ rad}$$

**2-22.** The triangular plate is fixed at its base, and its apex  $A$  is given a horizontal displacement of 5 mm. Determine the shear strain,  $\gamma_{xy}$ , at  $A$ .




$$L = \sqrt{800^2 + 5^2 - 2(800)(5) \cos 135^\circ} = 803.54 \text{ mm}$$

$$\frac{\sin 135^\circ}{803.54} = \frac{\sin \theta}{800}; \quad \theta = 44.75^\circ = 0.7810 \text{ rad}$$

$$\begin{aligned} \gamma_{xy} &= \frac{\pi}{2} - 2\theta = \frac{\pi}{2} - 2(0.7810) \\ &= 0.00880 \text{ rad} \end{aligned}$$


**Ans.**



**Ans:**

$$\gamma_{xy} = 0.00880 \text{ rad}$$


**2-23.** The triangular plate is fixed at its base, and its apex  $A$  is given a horizontal displacement of 5 mm. Determine the average normal strain  $\epsilon_x$  along the  $x$  axis.



$$L = \sqrt{800^2 + 5^2 - 2(800)(5) \cos 135^\circ} = 803.54 \text{ mm}$$

$$\epsilon_x = \frac{803.54 - 800}{800} = 0.00443 \text{ mm/mm}$$


**Ans.**



**Ans:**

$$\epsilon_x = 0.00443 \text{ mm/mm}$$


**\*2-24.** The triangular plate is fixed at its base, and its apex  $A$  is given a horizontal displacement of 5 mm. Determine the average normal strain  $\epsilon_{x'}$  along the  $x'$  axis.



$$L = 800 \cos 45^\circ = 565.69 \text{ mm}$$


$$\epsilon_{x'} = \frac{5}{565.69} = 0.00884 \text{ mm/mm}$$

**Ans.**





**2-25.** The square rubber block is subjected to a shear strain of  $\gamma_{xy} = 40(10^{-6})x + 20(10^{-6})y$ , where  $x$  and  $y$  are in mm. This deformation is in the shape shown by the dashed lines, where all the lines parallel to the  $y$  axis remain vertical after the deformation. Determine the normal strain along edge  $BC$ .



**Shear Strain:** Along edge  $DC$ ,  $y = 400$  mm. Thus,  $(\gamma_{xy})_{DC} = 40(10^{-6})x + 0.008$ .

Here,  $\frac{dy}{dx} = \tan(\gamma_{xy})_{DC} = \tan[40(10^{-6})x + 0.008]$ . Then,

$$\int_0^{\delta_C} dy = \int_0^{300 \text{ mm}} \tan[40(10^{-6})x + 0.008] dx$$

$$\delta_C = -\frac{1}{40(10^{-6})} \left\{ \ln \cos [40(10^{-6})x + 0.008] \right\} \Big|_0^{300 \text{ mm}}$$

$$= 4.2003 \text{ mm}$$

Along edge  $AB$ ,  $y = 0$ . Thus,  $(\gamma_{xy})_{AB} = 40(10^{-6})x$ . Here,  $\frac{dy}{dx} = \tan(\gamma_{xy})_{AB} = \tan[40(10^{-6})x]$ . Then,

$$\int_0^{\delta_B} dy = \int_0^{300 \text{ mm}} \tan[40(10^{-6})x] dx$$

$$\delta_B = -\frac{1}{40(10^{-6})} \left\{ \ln \cos [40(10^{-6})x] \right\} \Big|_0^{300 \text{ mm}}$$

$$= 1.8000 \text{ mm}$$


**Average Normal Strain:** The stretched length of edge  $BC$  is

$$L_{B'C'} = 400 + 4.2003 - 1.8000 = 402.4003 \text{ mm}$$

We obtain,

$$(\epsilon_{\text{avg}})_{BC} = \frac{L_{B'C'} - L_{BC}}{L_{BC}} = \frac{402.4003 - 400}{400} = 6.00(10^{-3}) \text{ mm/mm}$$


**Ans.**



**Ans:**

$$(\epsilon_{\text{avg}})_{BC} = 6.00(10^{-3}) \text{ mm/mm}$$

2-26. The Polysulfone block is glued at its top and bottom to the rigid plates. If a tangential force, applied to the top plate, causes the material to deform so that its sides are described by the equation  $y = 3.56x^{1/4}$ , determine the shear strain in the material at its corners  $A$  and  $B$ .



Prob. 2-33

$$y = 3.56 x^{1/4}$$

$$\frac{dy}{dx} = 0.890 x^{-3/4}$$

$$\frac{dx}{dy} = 1.123 x^{3/4}$$

At  $A$ ,  $x = 0$


$$\gamma_A = \frac{dx}{dy} = 0 \quad \text{Ans}$$

At  $B$ ,

$$2 = 3.56 x^{1/4}$$

$$x = 0.0996 \text{ mm}$$


$$\gamma_B = \frac{dx}{dy} = 1.123(0.0996)^{3/4} = 0.199 \text{ rad} \quad \text{Ans}$$



Ans:

$$(\epsilon_{\text{avg}})_{CA} = -5.59(10^{-3}) \text{ mm/mm}$$

**2-27.** The square plate  $ABCD$  is deformed into the shape shown by the dashed lines. If  $DC$  has a normal strain  $\epsilon_x = 0.004$ ,  $DA$  has a normal strain  $\epsilon_y = 0.005$  and at  $D$ ,  $\gamma_{xy} = 0.02$  rad, determine the shear strain at point  $E$  with respect to the  $x'$  and  $y'$  axes.



**Average Normal Strain:** The stretched length of sides  $DC$  and  $BC$  are

$$L_{DC'} = (1 + \epsilon_x)L_{DC} = (1 + 0.004)(600) = 602.4 \text{ mm}$$

$$L_{B'C'} = (1 + \epsilon_y)L_{BC} = (1 + 0.005)(600) = 603 \text{ mm}$$

Also,

$$\alpha = \frac{\pi}{2} - 0.02 = 1.5508 \text{ rad} \left( \frac{180^\circ}{\pi \text{ rad}} \right) = 88.854^\circ$$

$$\phi = \frac{\pi}{2} + 0.02 = 1.5908 \text{ rad} \left( \frac{180^\circ}{\pi \text{ rad}} \right) = 91.146^\circ$$

Thus, the length of  $C'A'$  and  $DB'$  can be determined using the cosine law with reference to Fig. *a*.

$$L_{C'A'} = \sqrt{602.4^2 + 603^2 - 2(602.4)(603) \cos 88.854^\circ} = 843.7807 \text{ mm}$$

$$L_{DB'} = \sqrt{602.4^2 + 603^2 - 2(602.4)(603) \cos 91.146^\circ} = 860.8273 \text{ mm}$$

Thus,

$$L_{E'A'} = \frac{L_{C'A'}}{2} = 421.8903 \text{ mm} \quad L_{E'B'} = \frac{L_{DB'}}{2} = 430.4137 \text{ mm}$$

Using this result and applying the cosine law to the triangle  $A'E'B'$ , Fig. *a*,


$$602.4^2 = 421.8903^2 + 430.4137^2 - 2(421.8903)(430.4137) \cos \theta$$

$$\theta = 89.9429^\circ \left( \frac{\pi \text{ rad}}{180^\circ} \right) = 1.5698 \text{ rad}$$

**Shear Strain:**

$$(\gamma_E)_{x'y'} = \frac{\pi}{2} - \theta = \frac{\pi}{2} - 1.5698 = 0.996(10^{-3}) \text{ rad}$$


**Ans.**




**Ans:**

$$(\gamma_E)_{x'y'} = 0.996(10^{-3}) \text{ rad}$$

**\*2-28.** The wire is subjected to a normal strain that is defined by  $\epsilon = (x/L)e^{-(x/L)^2}$ . If the wire has an initial length  $L$ , determine the increase in its length.



$$\begin{aligned}\Delta L &= \frac{1}{L} \int_0^L x e^{-(x/L)^2} dx \\ &= -L \left[ \frac{e^{-(x/L)^2}}{2} \right]_0^L = \frac{L}{2} [1 - (1/e)] \\ &= \frac{L}{2e} [e - 1]\end{aligned}$$



**Ans.**


2-29.

**Ans:**

$$(\epsilon_{\text{avg}})_{AC} = 0.0168 \text{ mm/mm},$$

$$(\gamma_A)_{xy} = 0.0116 \text{ rad}$$

**2-30.** The rectangular plate is deformed into the shape shown by the dashed lines. Determine the average normal strain along diagonal  $BD$ , and the average shear strain at corner  $B$ .



**Geometry:** The unstretched length of diagonal  $BD$  is

$$L_{BD} = \sqrt{300^2 + 400^2} = 500 \text{ mm}$$

Referring to Fig. *a*, the stretched length of diagonal  $BD$  is

$$L_{B'D'} = \sqrt{(300 + 2 - 2)^2 + (400 + 3 - 2)^2} = 500.8004 \text{ mm}$$

Referring to Fig. *a* and using small angle analysis,

$$\phi = \frac{2}{403} = 0.004963 \text{ rad}$$


$$\alpha = \frac{3}{300 + 6 - 2} = 0.009868 \text{ rad}$$

**Average Normal Strain:** Applying Eq. 2,

$$(\epsilon_{\text{avg}})_{BD} = \frac{L_{B'D'} - L_{BD}}{L_{BD}} = \frac{500.8004 - 500}{500} = 1.60(10^{-3}) \text{ mm/mm} \quad \text{Ans.}$$

**Shear Strain:** Referring to Fig. *a*,

$$(\gamma_B)_{xy} = \phi + \alpha = 0.004963 + 0.009868 = 0.0148 \text{ rad} \quad \text{Ans.}$$




**Ans:**

$$(\epsilon_{\text{avg}})_{BD} = 1.60(10^{-3}) \text{ mm/mm},$$

$$(\gamma_B)_{xy} = 0.0148 \text{ rad}$$

**2–31.** The nonuniform loading causes a normal strain in the shaft that can be expressed as  $\epsilon_x = kx^2$ , where  $k$  is a constant. Determine the displacement of the end  $B$ . Also, what is the average normal strain in the rod?



$$\frac{d(\Delta x)}{dx} = \epsilon_x = kx^2$$

$$(\Delta x)_B = \int_0^L kx^2 = \frac{kL^3}{3}$$

$$(\epsilon_x)_{\text{avg}} = \frac{(\Delta x)_B}{L} = \frac{\frac{kL^3}{3}}{L} = \frac{kL^2}{3}$$

**Ans.**




**Ans.**

**Ans:**

$$(\Delta x)_B = \frac{kL^3}{3}, (\epsilon_x)_{\text{avg}} = \frac{kL^2}{3}$$

**\*2-32** The rubber block is fixed along edge  $AB$ , and edge  $CD$  is moved so that the vertical displacement of any point in the block is given by  $v(x) = (v_0/b^3)x^3$ . Determine the shear strain  $\gamma_{xy}$  at points  $(b/2, a/2)$  and  $(b, a)$ .



**Shear Strain:** From Fig.  $a$ ,

$$\frac{dv}{dx} = \tan \gamma_{xy}$$

$$\frac{3v_0}{b^3}x^2 = \tan \gamma_{xy}$$

$$\gamma_{xy} = \tan^{-1}\left(\frac{3v_0}{b^3}x^2\right)$$

Thus, at point  $(b/2, a/2)$ ,

$$\gamma_{xy} = \tan^{-1}\left[\frac{3v_0}{b^3}\left(\frac{b}{2}\right)^2\right]$$

$$= \tan^{-1}\left[\frac{3}{4}\left(\frac{v_0}{b}\right)\right]$$


**Ans.**

and at point  $(b, a)$ ,

$$\gamma_{xy} = \tan^{-1}\left[\frac{3v_0}{b^3}(b^2)\right]$$


$$= \tan^{-1}\left[3\left(\frac{v_0}{b}\right)\right]$$

**Ans.**





**2-33.** The fiber  $AB$  has a length  $L$  and orientation  $\theta$ . If its ends  $A$  and  $B$  undergo very small displacements  $u_A$  and  $v_B$ , respectively, determine the normal strain in the fiber when it is in position  $A'B'$ .



**Geometry:**

$$\begin{aligned} L_{A'B'} &= \sqrt{(L \cos \theta - u_A)^2 + (L \sin \theta + v_B)^2} \\ &= \sqrt{L^2 + u_A^2 + v_B^2 + 2L(v_B \sin \theta - u_A \cos \theta)} \end{aligned}$$

**Average Normal Strain:**

$$\begin{aligned} \epsilon_{AB} &= \frac{L_{A'B'} - L}{L} \\ &= \sqrt{1 + \frac{u_A^2 + v_B^2}{L^2} + \frac{2(v_B \sin \theta - u_A \cos \theta)}{L}} - 1 \end{aligned}$$


Neglecting higher terms  $u_A^2$  and  $v_B^2$

$$\epsilon_{AB} = \left[ 1 + \frac{2(v_B \sin \theta - u_A \cos \theta)}{L} \right]^{\frac{1}{2}} - 1$$

Using the binomial theorem:

$$\begin{aligned} \epsilon_{AB} &= 1 + \frac{1}{2} \left( \frac{2v_B \sin \theta}{L} - \frac{2u_A \cos \theta}{L} \right) + \dots - 1 \\ &= \frac{v_B \sin \theta}{L} - \frac{u_A \cos \theta}{L} \end{aligned}$$

**Ans.**



**Ans.**

$$\epsilon_{AB} = \frac{v_B \sin \theta}{L} - \frac{u_A \cos \theta}{L}$$

**2-34.** If the normal strain is defined in reference to the final length, that is,

$$\epsilon'_n = \lim_{p \rightarrow p'} \left( \frac{\Delta s' - \Delta s}{\Delta s'} \right)$$

instead of in reference to the original length, Eq. 2-2, show that the difference in these strains is represented as a second-order term, namely,  $\epsilon_n - \epsilon'_n = \epsilon_n \epsilon'_n$ .

$$\begin{aligned} \epsilon_B &= \frac{\Delta s' - \Delta s}{\Delta s} \\ \epsilon_B - \epsilon'_A &= \frac{\Delta s' - \Delta s}{\Delta s} - \frac{\Delta s' - \Delta s}{\Delta s'} \\ &= \frac{\Delta s'^2 - \Delta s \Delta s' - \Delta s' \Delta s + \Delta s^2}{\Delta s \Delta s'} \\ &= \frac{\Delta s'^2 + \Delta s^2 - 2\Delta s' \Delta s}{\Delta s \Delta s'} \\ &= \frac{(\Delta s' - \Delta s)^2}{\Delta s \Delta s'} = \left( \frac{\Delta s' - \Delta s}{\Delta s} \right) \left( \frac{\Delta s' - \Delta s}{\Delta s'} \right) \\ &= \epsilon_A \epsilon'_B \text{ (Q.E.D)} \end{aligned}$$